



COBALT ALLOYS SAFETY DATA SHEET

1 of 11

Issue Date: 6/18/2015

Revision Date: 6/18/2015

SECTION: 1 IDENTIFICATION OF THE SUBSTANCE / MIXTURE AND OF THE COMPANY / UNDERTAKING

- 1.1 Product Name:** COBALT ALLOYS CAOTED, BARE AND CORED
Product Identification: ECoCr-C #1 Coated, ECoCr-A #6 Coated, ECoCr-B #12 Coated, ECoCr-E #21 Coated, ERCoCr-C #1 Bare, ERCoCr-A #6 Bare, ERCoCr-B #12 Bare, ERCoCr-E #21 Bare, ERCCoCr-C #1 Cored, ERCCoCr-A #6 Cored, ERCCoCr-B #12 Cored, ERCCoCr-E #21Cored
Product Specification: **AWS A5.13, A5.21**
- 1.2 Relevant identified uses of the substance or mixture and uses advised against:**
1.2.1 Relevant identified uses: For welding consumables and related products.
1.2.2 Uses advised: **Reference the [7. Handling and storage]**
- 1.3 Details of the supplier of the safety data sheet:**
Supplier: Weld Wire Company, Inc.
 103 Queens Drive
 King of Prussia, PA 19406
Emergency telephone number: (800) 523-1266 or (610) 265-3555
Email: info@weldwire.net

SECTION: 2 HAZARDS IDENTIFICATION

- 2.1 Classification of the mixture:**
 * **The product is placed on the market in solid form**
General Hazard Statement: Solid metallic products are generally classified as "articles" and do not constitute a hazardous material in solid form under the definitions of the OSHA Hazard Communication Standard (29 CFR 1910.1200). Any articles manufactured from these solid products would be generally classified as non-hazardous. However some hazardous elements contained in these products can be emitted under certain processing conditions such as but not limited to: burning, melting, cutting, sawing, brazing, grinding, machining, milling, and welding. Products in the solid state present no fire or explosion hazard. Small chips, fines, and dust may ignite readily, though. The following classification information is for the hazardous elements which may be released during processing.
- 2.1.1 Classification in accordance with GHS-US**
- | | | | |
|-----------------------|------|-------------------|-------|
| Acute Tox. 4 (Oral) | H302 | STOT SE 3 | H335 |
| Acute Tox. 4 (Dermal) | H312 | Carc. 1B | H350i |
| Skin Irrit. 2 | H315 | Carc. 2 | H351 |
| Skin Sens. 1 | H317 | Repr. Tox 2 | H361f |
| Eye Irrit. 2A | H319 | STOT RE 1 | H372 |
| Eye Irrit. 2B | H320 | Aquatic Acute 1 | H400 |
| Acute dust/mist 1,2 | H330 | Aquatic Chronic 1 | H410 |
| Resp. Sens. 1B | H334 | Aquatic Chronic 3 | H412 |

2.2 Label elements:

GHS-US labeling

Hazard Pictograms (GHS-US):



GHS07



GHS08



GHS09

Signal word (GHS-US): **Danger**

Hazard statements (GHS-US):

- H302** Harmful if swallowed
H312 Harmful in contact with skin
H315 Causes skin irritation
H317 May cause an allergic skin reaction
H319 Causes serious eye irritation
H320 Causes eye irritation
H330 Fatal if inhaled
H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled
H335 May cause respiratory irritation



COBALT ALLOYS

SAFETY DATA SHEET

2 of 11

- H350i** May cause cancer by inhalation
- H351** Suspected of causing cancer.
- H361f** Suspected of damaging fertility
- H372** Causes damage to organs through prolonged or repeated exposure
- H400** Very toxic to aquatic life
- H410** Very toxic to aquatic life with long lasting effects
- H412** Harmful to aquatic life with long lasting effects.

Precautionary statements:

- P201** Obtain special instructions before use
- P202** Do not handle until all safety precautions have been read and understood.
- P260** Do not breathe dust/fume/gas/mist/vapours/spray
- P261** Avoid breathing dust/fume/gas/mist/vapours/spray
- P264** Wash thoroughly after handling
- P270** Do not eat, drink or smoke when using this product.
- P272** Contaminated work clothing should not be allowed out of the workplace
- P273** Avoid release into the environment
- P280** Wear protective gloves/protective clothing/eye protection/face protection.
- P301+P312** IF SWALLOWED: call a POISON CENTER or doctor/physician if you feel unwell.
- P302+P352** IF ON SKIN: Wash with plenty of soap and water
- P308+P313** If exposed or concerned: Get medical advice/attention.
- P314** Get medical advice and attention if you feel unwell
- P321** Specific treatment (see label)
- P330** Rinse mouth
- P333+P313** If skin irritation or a rash occurs: Get medical advice/attention
- P362+P364** Take off contaminated clothing and wash before reuse
- P391** Collect spillage
- P405** Store locked up
- P501** Dispose of contents and container in accordance with local/regional/national/international regulations.

2.3 Hazards not otherwise classified (HNOC):

Welding Hazards: CAUTION. Welding will create fumes which may be toxic. If welding is performed on plated or coated materials such as galvanised or painted steel, excessive fume may be produced which contains additional hazardous components, and may result in metal fume fever or other health effects. The product and work surface will be hot during and after welding. Electric shock can kill. Arc Rays can injure eyes and burn skin.

Other Hazards: May be harmful if swallowed. Causes mild skin irritation. Very toxic to aquatic life with long lasting effects. Very toxic to aquatic life.

Unknown Acute Toxicity (GHS-US): 37.65% of the mixture consists of ingredient(s) of unknown toxicity.

SECTION: 3 COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Substances: No data available

Full text of H-phrases: see section 16

3.2 Mixtures: The mixture contains dangerous substances:

Substance name	Product Identifier (CAS No)	% Percent	GHS-US classification
Limestone (Calcium carbonate)	CaCO ₃ 1317-65-3	0.0 - 10.0	Not Classified
Chromium	Cr 7440-47-3	24.0-50.0	Acute Tox. 4 Oral (H302); Acute Tox. 4 Skin (H312); Skin Irrit. 2 (H315); Eye Irrit. 2B (H320)
Cobalt	Co 7440-48-4	25.0-50.0	Acute Tox. 4 Oral (H302), Acute dust/mist 1 (H330), Eye Irrit. 2A (H319), Resp. Sens. 1B (H334), Skin Sens. 1 (H317), Carc. 1B (H350i), Repr. Tox 2 (H361f), Aquatic Acute 1 (H400), Aquatic Chronic 1 (H410)
Fluorspar	CaF ₂ 7789-75-5	0.0-5.0	Acute Tox. 4 Oral (H302)



COBALT ALLOYS

SAFETY DATA SHEET

3 of 11

Iron	Fe	7439-89-6	0.0-5.0	Acute Tox. 4 Oral (H302)
Nickel	Ni	7440-02-0	0.0-4.0	Skin Sens. 1 (H317), Carc. 1B (H350i), STOT RE 1 (H372), Aquatic Chronic 3 (H412)
Potassium Oxide	K ₂ O	12136-45-7	0.0-2.0	Acute Tox. 4 Oral (H302)
Silica / Quartz	SiO ₂	14808-60-7	0.0-7.0	Carc. 1A (H350); STOT SE 3 (H335); STOT RE 1 (H372)
Sodium Oxide	Na ₂ O	1313-59-3	0.0-2.0	Carc. 1A (H350); STOT SE 3 (H335); STOT RE 1 (H372)
Carbon	C	7440-44-0	0.0-3.0	Not Classified
Silicon	Si	7440-21-3	0.0-2.0	Not Classified
Molybdenum	Mo	7439-98-7	0.0-7.0	Not Classified
Manganese	Mn	7439-96-5	0.0-2.0	Not Classified
Titanium dioxide	TiO ₂	13463-67-7	5.0-15.0	Carc. 2 (H351)
Tungsten	W	7440-33-7	0.0-16.0	Not Classified

SECTION: 4 FIRST AID MEASURES

4.1 Description of first aid measures:

General Advice: If symptoms persist, call a physician. Do not breathe dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing. In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

First-aid measures after inhalation: Move to fresh air. If breathing is irregular or stopped, administer artificial respiration. Oxygen or artificial respiration if needed. Get medical attention. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation.

First-aid measures after skin contact: Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. Wash off immediately with soap and plenty of water. Seek medical attention if irritation develops or persists.

First-aid measures after eye contact: Immediately flush eyes with water and continue washing for at least 15 minutes. Obtain medical attention if discomfort persists.

First-aid measures after ingestion: Do NOT induce vomiting. Drink plenty of water. Rinse mouth. If symptoms persist, call a physician. Get immediate medical attention.

Self-protection of the first aider: Self-protection of the first aider. Wear suitable gloves.

4.2 Most important symptoms and effects, both acute and delayed:

Symptoms/injuries after inhalation: Short-term (acute) overexposure to the gases, fumes, and dusts may include irritation of the eyes, lungs, nose, and throat. Some toxic gases associated with welding may cause pulmonary edema, asphyxiation, and death.

Acute overexposure may include signs and symptoms such as watery eyes, nose and throat irritation, headache, dizziness, difficulty in breathing, frequent coughing, or chest pain. The presence of chromium/chromate in fume can cause irritation of nasal membranes and skin. The presence of nickel compounds in fume can cause metallic taste, nausea, tightness of chest, fever, and allergic reaction. Excessive inhalation or ingestion of manganese can produce manganese poisoning. Overexposure to manganese compounds may affect the central nervous system, symptoms of which are languor, sleepiness, muscular weakness, emotional disturbances, and spastic gait resembling Parkinsonism. These symptoms can become progressive and permanent if not treated. Excessive inhalation of fumes may cause "Metal Fume Fever" with Flu-like symptoms such as chills, fever, body aches, vomiting, sweating, etc.

Symptoms/injuries after skin contact: Dusts may cause irritation.

Symptoms/injuries after eye contact: Causes eye irritation or damage.

Symptoms/injuries after ingestion: Not an anticipated route of exposure during normal product handling. May be harmful if ingested.

4.3 Indication of any immediate medical attention and special treatment needed:

Notes to Physician: Treat symptomatically. May cause sensitization by inhalation and skin contact. May cause sensitization of susceptible persons.

SECTION: 5 FIREFIGHTING MEASURES

5.1 Extinguishing media:

Suitable extinguishing media: Use extinguishing media appropriate for surrounding fire.

Unsuitable extinguishing media: No data available.

5.2 Special hazards arising from the substance or mixture:

Fire may produce irritating or poisonous gases. Non-combustible, substance itself does not burn but may decompose upon heating to produce corrosive and/or toxic fumes. Thermal decomposition can lead to release of irritating and toxic gases and vapors. May cause sensitization by inhalation and skin contact Carbon oxides.

Fire hazard: Not flammable

Explosion hazard: None known

5.3 Advice for firefighters:

In the event of fire, wear self-contained breathing apparatus and full protective gear.

Component Information:



COBALT ALLOYS

SAFETY DATA SHEET

4 of 11

Substance name	CAS number	Extinguishing Media for Fires (Suitable)	Extinguishing Media for Fires (Unsuitable)
Chromium	7440-47-3	Use extinguishing media appropriate for surrounding fire.	Do not use carbon dioxide, which may form an explosive mixture with powdered chromium.
Silicon	7440-21-3	SMALL FIRES: Dry chemical, sand, water spray, foam.; LARGE FIRES: Water spray, fog, foam	-----

SECTION: 6 ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures:

For non-emergency personnel: Wear appropriate personal protective equipment as specified in Section 8. Ensure adequate ventilation.

For emergency responders: No data available.

6.2 Environmental precautions: Avoid release into the environment. Avoid dispersal of spilled material and contact with soil, ground and surface water drains and sewers. See Section 12 for additional Ecological Information.

6.3 Methods and material for containment and cleaning up: Take up mechanically. Collect the material in labeled containers and dispose of according to local and regional authority requirements.

6.4 Reference to other sections: See Section 7 for information of safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

SECTION: 7 HANDLING AND STORAGE

7.1 Precautions and safe handling: Welding may produce dust, fumes and gases hazardous to health. Avoid breathing dust, fumes and gases. Use adequate ventilation. Keep away from sources of ignition. Avoid contact with skin, eyes and clothing. Do not eat, drink and smoke in work areas.

7.2 Conditions for safe storage, including and incompatibilities: Keep out of reach of children. Store in cool, dry and well-ventilated place. Keep away from incompatible materials. Keep away from heat and open flame.

7.3 Specific end use(s): For welding consumables and related products.

SECTION: 8 EXPOSURE CONTROLS / PERSONAL PROTECTION

8.1 Control parameters: Exposure limits were not established for this product

Substance name	CAS number	USA-ACGIH TLV	USA-OSHA PEL	USA-NIOSH IDLH
Cobalt	7440-48-4	0.02 mg/m ³ TWA	0.1 mg/m ³ TWA (dust and fume)	20 mg/m ³ IDLH (dust and fume)
Chromium	7440-47-3	0.5 mg/m ³ TWA	1 mg/m ³ TWA	250 mg/m ³ IDLH
Tungsten	7440-33-7	10 mg/m ³ STEL 5 mg/m ³ TWA	-----	-----
Nickel	7440-02-0	1.5 mg/m ³ TWA (inhalable fraction)	1 mg/m ³ TWA	10 mg/m ³ IDLH
Iron	7439-89-6	5 mg/m ³ TWA	5 mg/m ³ TWA	-----
Silicon	7440-21-3	-----	15 mg/m ³ TWA (total dust); 5 mg/m ³ TWA (respirable fraction)	not listed
Molybdenum	7439-98-7	10 mg/m ³ TWA (inhalable fraction); 3 mg/m ³ TWA (respirable fraction)	not listed	5000 mg/m ³ IDLH
Manganese	7439-96-5	0.02 mg/m ³ TWA (respirable fraction); 0.1 mg/m ³ TWA (inhalable fraction)	-----	500 mg/m ³ IDLH
Limestone (Calcium carbonate)	1317-65-3	2 mg/m ³ (Respirable Factor)	5 mg/m ³ TWA (Respirable Factor)	-----
Fluorspar	7789-75-5	2.5 mg/m ³	2.5 mg/m ³	-----
Potassium Oxide	12136-45-7	3 mg/m ³ (Respirable Factor)	5 mg/m ³ (Respirable Factor)	-----
Silica / Quartz	14808-60-7	0.1 mg/m ³ (Respirable Factor)	0.025 mg/m ³ (Respirable Factor)	-----



COBALT ALLOYS

SAFETY DATA SHEET

5 of 11

Sodium Oxide	1313-59-3	3 mg/m ³ (Respirable Factor)	5 mg/m ³ (Respirable Factor)	-----
Titanium dioxide	13463-67-7	10 mg/m ³	15 mg/m ³	-----

8.2 Other Exposure Guidelines: Hexavalent Chrome may be formed during welding.

Substance name	CAS number	Derived No Effect Level (DNEL)	Predicted No Effect Concentration (PNEC)
Cobalt	7440-48-4	0.04 mg/m ³ long term local inhalation	2.36 µg Co/l (AF 3) marine water; 0.74 µg/l (AF 3) fresh water
Chromium	7440-47-3	0.5 mg/m ³ local inhalation	-----
Tungsten	7440-33-7	5.8 mg/m ³ systemic inhalation	Tungsten 0.338 mg/l freshwater; 0.0338 mg/l marine water; 2.17 mg/kg soil; 11 mg/kg food
Nickel	7440-02-0	0.05 mg/m ³ local inhalation; 0.05 mg/m ³ systemic inhalation	0.0035-0.0218 mg/l freshwater; 0.0023 mg/l marine water
Iron	7439-89-6	3 mg/m ³ local inhalation	-----
Carbon	7440-44-0	10 mg/m ³ systemic inhalation	-----
Molybdenum	7439-98-7	11.17 mg/m ³ longterm local inhalation	-----
Manganese	7439-96-5	0.2 mg/m ³ systemic inhalation	-----

8.3 Engineering Controls

Appropriate engineering controls: Local exhaust and general ventilation must be adequate to meet exposure standards. Showers and Eyewash Stations.

8.4 Individual Protection Measures, such as Personal Protective Equipment

Hand protection: Wear welding gloves. The product and work surface will be hot during and after welding. Ensure adequate protection is in place to stop individuals from burning themselves.

Eye protection: Wear helmet or face shield with filter lens of appropriate shade number. See ANSI/ASC Z49.1 Section 4.2. Provide protective screens and flash goggles, if necessary, to shield others.

Skin and body protection: Wear head and body protection, which help to prevent injury from radiation, sparks, flame and electrical shock. See ANSI Z49.1. At a minimum this includes welder's gloves and a protective face shield, and may include arm protectors, aprons, hats, shoulder protection, as well as dark substantial clothing. Train the employee not to touch live electrical parts and to insulate him/herself from work and ground. Welders should not wear short sleeve shirts or short pants.

Respiratory protection: Use only with adequate ventilation. If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations.

Hygiene Measures: Handle in accordance with good industrial hygiene and safety practice. Do not eat, drink or smoke when using this product. Regular cleaning of equipment, work area and clothing is recommended. Keep away from food, drink and animal feeding stuffs. Avoid contact with skin, eyes and clothing. Wash hands before breaks and at the end of workday.

8.5 Biological Standards

Substance name	CAS number	USA ACGIH -BEI
Cobalt	7440-48-4	15 µg/L Medium: urine Time: end of shift at end of workweek Parameter: Cobalt (nonspecific)

SECTION: 9 PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties:

Physical State:	- Solid	Appearances:	- Rods or wire
Odor:	- Odorless	Melting point / Melting range:	- 1285 - 1395 °C / 2340 - 2540 °F
Flash point:	- Not applicable	Vapor Pressure:	- Not applicable
Vapor Density:	- Not applicable	Water Solubility:	- Insoluble in water
Dynamic viscosity:	- Solid	Density:	- 8.44 g/cm ³

9.2 Other information:

VOC Content(%) Not Applicable

Substance name	CAS number	Mol. Weight	Water Solub.	Vap. Press.	Vap. Dens.	pH Val.	Autoign. Temp.	Evap. Rate	Boil. Temp.
Cobalt	7440-48-4	58.93 g/mol	---	0.00007 hPa at 1050 °C	---	---	---	---	2870 °C



COBALT ALLOYS

SAFETY DATA SHEET

6 of 11

Chromium	7440-47-3	51.99 g/mol	---	---	---	---	---	---	2642 °C
Molybdenum	7439-98-7	95.95 g/mol	0 mg/L at 20°C	---	---	---	---	---	4612 °C at 101.3 hPa
Nickel	7440-02-0	58.69 g/mol	---	1 mmHg at 1810 °C	---	---	---	---	---
Silicon	7440-21-3	28.08 g/mol	<1 mg/L	---	---	---	---	---	---
Iron	7439-89-6	55.84 g/mol	---	0.000001 hPa at 25 °C	---	---	>100 °C	---	---
Manganese	7439-96-5	54.93 g/mol	---	1 mmHg at 1292 °C	---	---	---	---	---
Carbon	7440-44-0	12.01 g/mol	---	---	---	---	300 - 500 °C	---	---
Tungsten	7440-33-7	183.84 g/mol	---	0.00000001hPa at 1700°C	---	---	---	---	---

Substance name	CAS number	Density VALUE	Melt. Temp.	Flash Point	Water Sol.	Bulk Dens.	Odor	State	Color
Cobalt	7440-48-4	8.85 - 8.9g/cm ³ at 20°C	< 1495 °C	---	soluble	---	---	---	---
Chromium	7440-47-3	7.19 g/cm ³ at 20 °C	1900 °C	---	insoluble	---	---	---	Grey
Molybdenum	7439-98-7	10.2 g/cm ³ at 20 °C	2617 °C (sublimes)	---	insoluble	---	---	---	---
Nickel	7440-02-0	8.9 g/cm ³ at 25 °C	---	---	insoluble	---	---	---	---
Silicon	7440-21-3	2.33 g/cm ³ at 25 °C	1410 °C	---	---	---	---	---	Dark Grey; Dark Brown
Iron	7439-89-6	7.87 g/cm ³ at 25 °C	1539 °C	---	insoluble	3000 - 4000 kg/m ³	---	---	---
Carbon	7440-44-0	---	≥ 3500 °C	---	insoluble	0.25 -0.75kg/m ³ at 20°C	---	---	---
Tungsten	7440-33-7	19.3 g/cm ³ at 20 °C	3422 °C	---	slightly soluble	2100 - 9000 kg/m ³	---	---	---

SECTION: 10 STABILITY AND REACTIVITY

- 10.1 Reactivity:** Stable under normal conditions
- 10.2 Chemical stability:** The product is stable under normal conditions. When using it may produce dangerous fumes and gases.
- 10.3 Possibility of hazardous reactions:** None under normal processing.
- 10.4 Conditions to avoid:** Keep away from sources of heat (e.g. hot surfaces), sparks and open flames.
- 10.5 Incompatible materials:** Acids. Strong oxidizing agents.
- 10.6 Hazardous decomposition products:** Thermal decomposition can lead to release of toxic/corrosive gases and vapors. Welding fumes and gases cannot be classified simply. The composition and quantity of both are dependent upon the metal being welded, the process, procedure and welding consumables used. Other conditions which also influence the composition and quantity of the fumes and gases to which workers may be exposed include: coating on the metal being welded (i.e. paint, painting, galvanizing), the number of welders, the volume of the work area, the quality and the amount of ventilation, the position of the welders head with respect to the fume plume, as well as the presence of contaminants in the atmosphere (such as chlorinated hydrocarbon vapors from the cleaning and degreasing activities).
- When an electrode is consumed, the fume and gas decomposition products generated are different in percent and form from the ingredients listed in Section 3. Fume and gas decomposition, and not the ingredients in the electrode, are important. The concentration of a given fume or gas component may decrease or increase by many times the original concentration. Also, new compounds not in the electrodes may form.
- Decomposition products of normal operation include those originating from the volatilization, reaction or oxidation of the materials shown in Section 3, plus those from the base metal coating, etc., as noted above. Reasonable expected fume constituents of this product would include: Complex oxides of iron, manganese, silicon, chromium, nickel, columbium, molybdenum, copper, carbon dioxide, carbon monoxide, ozone and nitrogen oxides. Some products will also contain antimony, barium, molybdenum, aluminum, columbium, magnesium, strontium, tungsten, and or zirconium. Fume limit for chromium, nickel and or manganese may be reached before limit of 5 mg/m³ of general welding fumes is reached.
- Gaseous reaction products may include carbon monoxide and carbon dioxide. Ozone and nitrogen oxides may be formed by the radiation from the arc. Determine the composition and quantity of fumes and gases to which workers are exposed by taking an air sample from inside the welder's helmet if worn or in the worker's breathing zone. Improve ventilation if exposures are not below limits. See ANSI/AWS F1.1, F1.3 and F1.5, available from the American Welding Society, 550 N.W. LeJeune Road, Miami, FL 33126.



COBALT ALLOYS

SAFETY DATA SHEET

7 of 11

SECTION: 11 TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects:

Acute toxicity: Harmful if swallowed

Inhalation: May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Eye Contact: May cause eye irritation with susceptible persons.

Skin contact: Repeated or prolonged skin contact may cause allergic reactions with susceptible persons. Prolonged contact may cause redness and irritation. Prolonged skin contact may defat the skin and produce dermatitis. May cause sensitization by skin

Ingestion: Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea. Ingestion may cause irritation to mucous membranes.

Substance name	CAS number	LD50 oral	LD50 Dermal	LC50 Inhalation (mg/l)
Chromium	7440-47-3	>5000 mg/kg bw	Data waiving-sutdy unjustified	>5.41 mg/l/air
Cobalt	7440-48-4	550 mg/kg bw	>2000 mg/kg bw	0.05 mg/l
Tungsten	7440-33-7	>2000 mg/kg bw	>2000 mg/kg bw	>5.4 mg/l/air
Nickel	7440-02-0	>9000 mg/kg bw	Data waiving-other justification	NOAEC >=10.2 mg/l/air
Iron	7439-89-6	984 mg/kg rat	-- --	-- --
Carbon	7440-44-0	>10000 mg/kg rat	-- --	-- --
Silicon	7440-21-3	3160 mg/kg bw	>5000 mg/kg bw	Acutely Non Toxic
Molybdenum	7439-98-7	>2000 mg/kg bw	Not Classified	>3.92 mg/l/air
Manganese	7439-96-5	>2000 mg/kg bw	Data waiving-sutdy unjustified	>5.14 mg/l/air

Information on toxicological effects

Substance name	CAS number	U.S. ACGIH - Critical Effects
Chromium	7440-47-3	skin and upper respiratory tract irritation
Cobalt	7440-48-4	asthma: myocardial effects; pulmonary function
Tungsten	7440-33-7	lower respiratory tract irritation
Nickel	7440-02-0	dermatitis; pneumoconiosis
Manganese	7439-96-5	CNS impairment

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation: Repeated or prolonged contact may cause allergic reactions, redness and irritation

Serious eye damage/irritation: May cause eye irritation with susceptible persons

Respiratory: May cause allergy or asthma symptoms or breathing difficulties if inhaled

Germ cell mutagenicity: Not classified

Carcinogenicity: May cause cancer. This product contains one or more substances which are classified by IARC as carcinogenic to humans (Group I), probably carcinogenic to humans (Group 2A) or possibly carcinogenic to humans (Group 2B).

Substance name	CAS number	Agency	Risk Factor
Cobalt	7440-48-4	ACGIH	A3- Confirmed Animal Carcinogen with Unknown Relevance to Humans
		IARC Group	2B- Possibly carcinogenic to humans
		National Toxicology Program (NTP) Status	Clear evidence in rodents tested
Chromium	7440-47-3	ACGIH	A4- Not classifiable as a Human Carcinogen
		IARC Group	3- Not classifiable as to its carcinogenicity to humans
		National Toxicology Program (NTP) Status	Long term exposure technical reports were not prepared
Tungsten	7440-33-7	National Toxicology Program (NTP) Status	Short term exposure studies in progress
Nickel	7440-02-0	ACGIH	A5- Not Suspected as a Human Carcinogen
		IARC Group	1- Carcinogenic to humans
		IARC Group	2B- Possibly carcinogenic to humans
		National Toxicology Program (NTP) Status	3- Reasonably anticipated to be Human Carcinogen



COBALT ALLOYS

SAFETY DATA SHEET

8 of 11

- Reproductive toxicity:** Contains a known or suspected reproductive toxin. Prolonged exposure may cause chronic effects. CNS and psychiatric effects, Parkinson-like symptoms. Languor, sleepiness and weakness in legs. A stolid masklike appearance of face, emotional disturbances such as uncontrollable laughter and spastic gait with tendency to fall in walking and findings in more advanced cases. Repeated contact may cause allergic reactions in very susceptible persons. Avoid repeated exposure. Repeated or prolonged skin contact may cause skin irritation and/or dermatitis and sensitization of susceptible persons. Repeated or prolonged exposure may cause central nervous system damage. Contains a known or suspected reproductive toxin. This product contains one or more substances which are classified by IARC as carcinogenic to humans (Group I), probably carcinogenic to humans (Group 2A) or possibly carcinogenic to humans (Group 2B).
- Chronic toxicity:**
- Target organ effects:** Blood, Central Nervous System (CNS), Central Vascular System (CVS), Eyes, Kidney, Liver, Lungs, Nasal Cavities, Respiratory System, Skin.
- Neurological effects:** Repeated or prolonged exposure may cause central nervous system damage. Prolonged or excessive exposure to manganese in dust or fume may cause irreversible central nervous system damage (Manganism). Symptoms resemble Parkinson's disease and include tremors, impaired speech, mask like face and impaired movement.

Numerical measures of toxicity: No data available

The following values are calculated based on chapter 3.1 of the GHS document

ATE mix (oral): 508 mg/kg

ATE mix (dermal): 5 mg/kg

ATE mix (inhalation-gas): 10 mg/l

SECTION: 12 ECOLOGICAL INFORMATION

- 12.1 Ecology Toxicity:** 96% of the mixture consists of components(s) of unknown hazards to the aquatic environment
- 12.2 Persistence and degradability:** No additional information available.
- 12.3 Bioaccumulative potential:** No additional information available.
- 12.4 Results of PBT and vPvB assessment:** The components in this formulation do not meet the criteria for classification as PBT or vPvB
- 12.5 Other adverse effects:** No additional information available.

SECTION: 13 DISPOSAL CONSIDERATIONS

- 13.1 Waste treatment methods:** It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste identification and disposal methods in compliance with applicable regulations. It must undergo special treatment, e.g. at suitable disposal site, to comply with local regulations.
- 13.2 Waste from residues/unused products:** Reuse or recycle. Recover or recycle if possible. Dispose of in accordance with local regulations.
- 13.3 Contaminated packaging:** Empty containers should be taken to an approved waste handling site for recycling or disposal.
- 13.4 California waste Status:** This product contains one or more substances that are listed with the State of California as a hazardous waste.

Substance name	CAS number	CALIFORNIA HAZARDOUS WASTE STATUS
Chromium	7440-47-3	Toxic; Corrosive; Ignitable
Cobalt	7440-48-4	Toxic; Ignitable
Nickel	7440-02-0	Toxic; Ignitable
Molybdenum	7439-98-7	Ignitable
Manganese	7439-96-5	Ignitable

SECTION: 14 TRANSPORT INFORMATION

In accordance with DOT / ADR / RID / ADNR / IMDG / ICAO / IATA

14.1 UN Number: Not a dangerous good in sense of transport regulations

14.2 UN proper shipping name: Not applicable

Substance name	CAS number	U.S. - DOT Reportable Quantities	DOT Marine Pollutant	DOT Severe Marine Pollutant
Chromium	7440-47-3	5000 lbs RQ (The RQ for these hazardous substances is limited to those pieces of the metal having a diameter smaller than 100 µm (0.004 inches).); 2270 kg RQ (The RQ for these hazardous substances is limited to those pieces of the metal having a diameter smaller than 100 µm (0.004 inches).)	-----	-----
Nickel	7440-02-0	100 lbs RQ (The RQ for these hazardous substances is limited to those pieces of the metal having a diameter smaller than 100 µm (0.004 inches).); 45.4 kg RQ (The RQ for these hazardous substances is limited to those pieces of the metal having a diameter smaller than 100 µm (0.004 inches).)	-----	-----



COBALT ALLOYS

SAFETY DATA SHEET

9 of 11

SECTION: 15 REGULATORY INFORMATION

15.1 US Federal Regulations:

Substance name	CAS number	WEIGHT%	U.S. Toxic Substances Control Act (TSCA)	SARA 313- Threshold Values
Chromium	7440-47-3	24.0-50.0	Present	Present
Cobalt	7440-48-4	25.0-50.0	Present	Present
Tungsten	7440-33-7	0.0-16.0	Present	-----
Nickel	7440-02-0	0.0-4.0	Present	-----
Iron	7439-89-6	0.0-5.0	Present	-----
Carbon	7440-44-0	0.0-3.0	Present	-----
Silicon	7440-21-3	0.0-2.0	Present	-----
Molybdenum	7439-98-7	0.0-7.0	Present	-----
Manganese	7439-96-5	0.0-2.0	Present	-----

SARA 311/312 Hazard

Acute Health Hazard	yes
Chronic Health Hazard	yes
Fire Hazard	no
Sudden Release of Pressure Hazard	no
Reactive Hazard	no

Clean Water Act:

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

Substance name	CAS number	CWA- Reportable Quantities	CWA- Toxic Pollutants	CWA- Priority Pollutants	CWA-Hazardous Substances
Chromium	7440-47-3	Not Applicable	Present	Present	Not Applicable
Nickel	7440-02-0	Not Applicable	Present	Present	Not Applicable

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Substance name	CAS number	Hazardous Substances RQs	Extremely Hazardous Substances RQs	RQ
Chromium	7440-47-3	5000 lb final RQ (no reporting of releases of this hazardous substance is required if the diameter of the pieces of the solid metal released is >100 µm); 2270 kg final RQ (no reporting of releases of this hazardous substance is required if the diameter of the pieces of the solid metal released is >100 µm)	-----	5000 lb final RQ (no reporting of releases of this hazardous substance is required if the diameter of the pieces of the solid metal released is >100 µm); 2270 kg final RQ (no reporting of releases of this hazardous substance is required if the diameter of the pieces of the solid metal released is >100 µm)
Nickel	7440-02-0	100 lb final RQ (no reporting of releases of this hazardous substance is required if the diameter of the pieces of the solid metal released is >100 µm); 45.4 kg final RQ (no reporting of releases of this hazardous substance is required if the diameter of the pieces of the solid metal released is >100 µm)	-----	100 lb final RQ (no reporting of releases of this hazardous substance is required if the diameter of the pieces of the solid metal released is >100 µm); 45.4 kg final RQ (no reporting of releases of this hazardous substance is required if the diameter of the pieces of the solid metal released is >100 µm)



COBALT ALLOYS

SAFETY DATA SHEET 10 of 11

15.2 US State Regulations:

California Proposition 65: This product contains the following Proposition 65 chemicals:

Substance name	CAS number	California - Proposition 65 - Carcinogens List	California - Proposition 65 - Developmental Toxicity	California - Proposition 65 - Reproductive Toxicity	California - 22 CCR - Toxic and Extremely Hazardous Carcinogenic Wastes
Cobalt	7440-48-4	Carcinogen, initial date 7/1/92 (powder)	-----	-----	-----
Nickel	7440-02-0	Carcinogen, initial date 10/1/89 (metallic)	-----	-----	-----

15.3 US State Right-to-Know Regulations:

Substance name	CAS number	New Jersey	Massachusetts	Pennsylvania
Cobalt	7440-48-4	sn 0520	Present	Environmental hazard (fume) Present
Chromium	7440-47-3	sn 0432	Carcinogen; Extraordinarity Hazardous	Environmental hazard; Special Hazardous Substance Present
Tungsten	7440-33-7	sn 1959	Present	Present
Nickel	7440-02-0	sn 1341 (dust and fume)	Carcinogen; Extraordinarity Hazardous	Environmental hazard; Special Hazardous Substance Present
Silicon	7440-21-3	sn 3125 (powder)	Present (dust, exempt when encapsulated or if particulates are not present and cannot be substantially generated through use of the product)	Present
Molybdenum	7439-98-7	sn 1309	Present	Present
Manganese	7439-96-5	sn 1155 (dust and fume)	Present	Environmental Hazard Present

SECTION: 16 OTHER INFORMATION

Full text of H-phrases:

Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Acute Tox. 4 (Dermal)	Acute toxicity (Dermal), Category 4
Acute dust/mist 1	Acute toxicity (Inhalation), Category 1
Aquatic Acute 1	Hazardous to the aquatic environment — Acute Hazard, Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment — Chronic Hazard, Category 1
Aquatic Chronic 3	Hazardous to the aquatic environment — Chronic Hazard, Category 3
Carc. 1A	Carcinogenicity, Category 1A
Carc. 1B	Carcinogenicity, Category 1B
Carc. 2	Carcinogenicity, Category 2
Eye Irrit. 2A	Serious eye damage/eye irritation, Category 2A
Eye Irrit. 2B	Serious eye damage/eye irritation, Category 2B
Repr. Tox 2	Reproductive toxicity, Category 2
Resp. Sens. 1B	Sensitisation — Respiratory, Category 1B
Skin Sens. 1	Sensitisation — Skin, Category 1
Skin Irrit. 2	Skin corrosion/irritation, Category 2
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3,
STOT RE 1	Specific target organ toxicity — Repeated exposure, Category 1
H302	Harmful if swallowed
H312	Harmful in contact with skin
H315	Causes skin irritation
H317	May cause an allergic skin reaction



COBALT ALLOYS


SAFETY DATA SHEET 11 of 11

H319	Causes serious eye irritation
H320	Causes eye irritation
H330	Fatal if inhaled
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled
H335	May cause respiratory irritation
H350	May cause cancer
H350i	May cause cancer by inhalation
H351	Suspected of causing cancer.
H361f	Suspected of damaging fertility
H372	Causes damage to organs through prolonged or repeated exposure
H400	Very toxic to aquatic life
H410	Very toxic to aquatic life with long lasting effects
H412	Harmful to aquatic life with long lasting effects.

NFPA health hazard: 2 - Intense or continued exposure could cause temporary incapacitation or possible residual injury unless prompt medical treatment is given.

NFPA fire hazard: 0 - Materials that will not burn.

NFPA reactivity: 0 - Normally stable, even under fire exposure conditions, and are not reactive with water.



HMIS III Rating

Health: 2- Moderate Hazard - Temporary or minor injury may occur

Flammability: 0- Minimal Hazard

Physical: 0- Minimal Hazard

We believe that the information contained herein is believed to be true and accurate as of the date of this SDS. All statements or suggestions are made without any warranty, expressed or implied, regarding the accuracy of the information, the hazard connected with the use of this material or the results to be obtained for use thereof. As the condition or methods of use are beyond our control, we do not assume any responsibility and expressly disclaim any liability for any use of this material. It is the user's obligation to determine the conditions of safe use of these products.

All chemical products can in fact present unknown risks to health, safety and / or the environment, even in relation to the different operating conditions, and they must therefore be used with care. For this reason we cannot guarantee that the risk described in this form are the only foreseeable risks. The user must therefore satisfy himself as to the particular conditions under which it is intended to be use in. Moreover, it must be noted that the user is obliged to comply with all the legislative, administrative and regulatory provisions regarding the product and its use in terms of occupational hygiene and safety, and environmental protection, apart from the information given in the form, given purely as guidance.

Technical Department