WELDWIRE

CAST IRON

SAFETY DATA SHEET 1 of 7

TION	: 1	IDENTIFICATION OF THE	SUBSTANCE / MIXTURE AND OF THE COMPANY / UNDERTAKIN
1.1	Product Name	CA	ST IRON
	Product Identi	fication: 44	NiFeMn-CI, 55 NiFe-CI, 99 Ni-CI, NICORE55
	Product Specif	cation: AV	VS A5.15, NO CLASSIFICATION
1.2	Relevant ident	ified uses of the substance of	or mixture and uses advised against:
1.2.1	Relevant ident	ified uses: For	welding consumables and related products.
1.2.2	Uses advised:	Re	ference the [7. Handling and storage]
1.3	Details of the s	supplier of the safety data sh	neet:
	Supplier:	We	ld Wire Company, Inc.
		103	3 Queens Drive
		Kin	g of Prussia, PA 19406
	Emergency tel	ephone number: (80	00) 523-1266 or (610) 265-3555
	Email:	info	p@weldwire.net
TION	: 2	HAZARDS IDENTIFICATI	οΝ
2.1	Classification of	of the mixture:	
		t is placed on the market in solid	d form
2.1.1	Classification i	n accordance with GHS-US	
	Skin Sens.	1 H317	
	Carc. 1B	H350	
	STOT RE 1	H372	
	Aquatic Acu	ite 1 H400	
	Aquatic Chr	onic 3 H412	
2.2	Label elements		
	GHS-US la	beling	
	Hazard Pi	ctograms (GHS-US):	
			GHS07 GHS08 GHS09
	Signal wo	rd (GHS-US): Danger	
	Hazard st	atements (GHS-US):	
	H317	May cause an allergic skin react	ion
	H350	May cause cancer	
	H372	Causes damage to organs throu	gh prolonged or repeated exposure
	H400	Very toxic to aquatic life	
	H412	Harmful to aquatic life with long	lasting effects.
	Precautio	nary statements:	
	P201	Obtain special instructions befor	'e use
	P202	Do not handle until all safety pre	ecautions have been read and understood.
	P260	Do not breathe dust/fume/gas/r	nist/vapours/spray
	P261	Avoid breathing dust/fume/gas/	mist/vapours/spray
	P264	Wash thoroughly after handling	
		Do not eat, drink or smoke whe	
	P272	Contaminated work clothing sho	ould not be allowed out of the workplace
	P273	Avoid release into the environm	ent
	P280	Wear protectective gloves/prote	ctive clothing/eye protection/face protection.
	P302+P3	52 IF ON SKIN: Wash with p	enty of saop and water
		13 If exposed or concerned:	Get medical advice/attention.
	P308+P3		
		Get medical advice and attention	n if you feel unwell
			occurs: Get medical advice/attention
	P314	13 If skin irritation or a rash	5
	P314 P333+P3 P362+P36 P391	13 If skin irritation or a rash	occurs: Get medical advice/attention
	P314 P333+P3 P362+P36 P391	13 If skin irritation or a rash54 Take off contaminated clear	occurs: Get medical advice/attention



CAST IRON SAFETY DATA SHEET ^{2 of 7}

2.3 Other hazards: No additional information available

2.4 Unknown acute toxicity (GHS-US): No data available.

SECTION: 3 COMPOSITION/INFORMATION ON INGREDIENTS

Substances: No data available

3.1

Full text of H-phrases: see section 16

3.2 Mixtures: The mixture contains dangerous substances:

Substance name		Product Identifier (CAS No)	% Percent	GHS-US classification
Nickel	Ni	7440-02-0	35 - 85	Skin Sens. 1, H317 Car. 1B, H350 STOTT RE 1, H372
Iron	Fe	7439-89-6	0.08 - 41.97	Acute Tux. 4 (Oral), H302
Manganese	Mn	7439-96-5	2.5 - 14	Not classified
Silicon	Si	7440-21-3	1 - 3	Not classified
Copper	Cu	7440-50-8	2.5	Not classified
Aluminum	AI	7429-90-5	1	Not classified
Carbon	C	7440-44-0	0.055 - 0.15	Not classified

SECTION: 4 FIRST AID MEASURES

4.1 Description of first aid measures:

First-aid measures after inhalation: Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention.

First-aid measures after skin contact: Flush with water for at least 15 minutes. Seek medical attention if irritation develops or persists.

First-aid measures after eye contact: Immediately flush eyes with water and continue washing for at least 15 minutes. Obtain medical attention if discomfort persists.

First-aid measures after ingestion: Do NOT induce vomiting. Get immediate medical attention.

4.2 Most important symptoms and effects, both acute and delayed:

Symptoms/injuries after inhalation: Short-term (acute) overexposure to the gases, fumes, and dusts may include irritation of the eyes, lungs, nose, and throat. Some toxic gases associated with welding may cause pulmonary edema, asphyxiation, and death. Acute overexposure may include signs and symptoms such as watery eyes, nose and throat irritation, headache, dizziness, difficulty in breathing, frequent coughing, or chest pain. The presence of chromium/chromate in fume can cause irritation of nasal membranes and skin. The presence of nickel compounds in fume can cause metallic taste, nausea, tightness of chest, fever, and allergic reaction. Excessive inhalation or ingestion of manganese can produce manganese poisoning. Overexposure to manganese compounds may affect the central nervous system, symptoms of which are languor, sleepiness, muscular weakness, emotional disturbances, and spastic gait resembling Parkinsonism. These symptoms can become progressive and permanent if not treated. Excessive inhalation of fumes may cause "Metal Fume Fever" with Flu-like symptoms such as chills, fever, body aches, vomiting, sweating, etc.

Symptoms/injuries after skin contact: Dusts may cause irritation.

Symptoms/injuries after eye contact: Causes eye irritation.

Symptoms/injuries after ingestion: Not an anticipated route of exposure during normal product handling. May be harmful if ingested.

4.3 Indication of any immediate medical attention and special treatment needed: No data available.

SECTION: 5	5 FIREFIGHTING MEASURES	
5.1 E	Extinguishing media:	
	Suitable extinguishing media: Use extinguishing	media appropriate for surrounding fire.
	Unsuitable extinguishing media: No data availab	le.
5.2 \$	Special hazards arising from the substance or mixtu	Ire: Fire may produce irritating or poisonous gases.
	Fire hazard:	Not flammable
	Explosion hazard:	None known
5.3 A	Advice for firefighters: In the event of fire, wear self-co	ontained breathing apparatus and full protective gear.
SECTION: 6	6 ACCIDENTAL RELEASE MEASURE	S

6.1 Personal precautions, protective equipment and emergency procedures:

For non-emergency personnel: Wear appropriate personal protective equipment as specified in Section 8. Ensure adequate ventilation.



SAFETY DATA SHEET ^{3 of 7}

For emergency responders: No data available.

- 6.2 Environmental precautions: Avoid release into the environment. Avoid dispersal of spilled material and contact with soil, ground and surface water drains and sewers.
- 6.3 Methods and material for containment and cleaning up: Take up mechanically. Collect the material in labeled containers and dispose of according to local and regional authority requirements.
- 6.4 **Reference to other sections:** See Section 7 for information of safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

SECTION: 7 HANDLING AND STORAGE

- 7.1 Precautions and safe handling: Welding may produce dust, fumes and gases hazardous to health. Avoid breathing dust, fumes and gases. Use adequate ventilation. Keep away from sources of ignition. Avoid contact with skin, eyes and clothing. Do not eat, drink and smoke in work areas.
- 7.2 Conditions for safe storage, including and incompatibilities: Store in cool, dry and well-ventilated place. Keep away from incompatible materials. Keep away from heat and open flame.
- 7.3 Specific end use(s): For welding consumables and related products.

SECTION: 8 EXPOSURE CONTROLS / PERSONAL PROTECTION

8.1 Control parameters: Exposure limits were not established for this product

Nickel	(CAS No) 7440-02-0	
USA ARCGIS	ARCGIS TWA (mg/m ³)	1.5 mg/m ³
USA OSHA	OSHA PEEL (TWA) (mg/m³)	1 mg/m ³
Silicon	(CAS No) 7440-21-3	
USA OSHA	OSHA PEEL TWA (mg/m³)	5 mg/m ³
Manganese	(CAS No) 7439-96-5	
USA ARCGIS	ARCGIS TWA (mg/m³)	0.1 mg/m ³
USA OSHA	OSHA PEEL (Ceiling) (mg/m ³)	5 mg/m ³
Aluminum	(CAS No) 7429-90-5	
USA ARCGIS	ARCGIS TWA (mg/m ³)	1 mg/m ³
USA OSHA	OSHA PEEL (TWA) (mg/m³)	5 mg/m ³
Copper	(CAS No) 7440-50-8	
USA ARCGIS	ARCGIS TWA (mg/m ³)	0.2 mg/m ³
USA OSHA	OSHA PEEL (TWA) (mg/m³)	1 mg/m ³

8.2 Exposure controls:

Appropriate engineering controls: Local exhaust and general ventilation must be adequate to meet exposure standards. Hand protection: Wear welding gloves.

Eye protection: Wear helmet or face shield with filter lens of appropriate shade number. See ANSI/ASK Z49.1 Section 4.2. Provide protective screens and flash goggles, if necessary, to shield others.

Skin and body protection: Wear head and body protection, which help to prevent injury from radiation, sparks, flame and electrical shock. See ANSI Z49.1. At a minimum this includes welder's gloves and a protective face shield, and may include arm protectors, aprons, hats, shoulder protection, as well as dark substantial clothing. Train the employee not to touch live electrical parts and to insulate him/herself from work and ground. Welders should not wear short sleeve shirts or short pants.

Respiratory protection: If exposure limits are exceeded or irritation is experienced, NOSH approved respiratory protection should be worn.

SECTION: 9 PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties:

Physical state:	- Solid
Appearances:	- Rods or wire
Color:	- Metallic
Odor:	- No data available
Odor threshold:	- No data available
pH:	- No data available
Relative evaporation rate (butyl acetate=1):	- No data available



SAFETY DATA SHEET 4 of 7

Melting point:	- No data available
Freezing point:	- No data available
Initial boiling point and boiling range:	- No data available
Flash point:	- No data available
Self ignition temperature:	- No data available
Decomposition temperature:	- No data available
Flammability (solid, gas):	- No data available
Vapor pressure:	- No data available
Relative vapor density at 20° C:	- No data available
Relative density:	- No data available
Solubility(is)	- No data available
Log Pow:	- No data available
Log Know:	- No data available
Viscosity, kinematic:	- No data available
Viscosity, dynamic:	- No data available
Explosive properties:	- No data available
Oxidizing properties:	- No data available
Explosive limits:	- No data available

9.2 Other information: No additional information available.

SECTION: 10

STABILITY AND REACTIVITY

- **10.1 Reactivity:** No additional information available.
- 10.2 Chemical stability: The product is stable under normal conditions. When using it may produce dangerous fumes and gases.
- 10.3 Possibility of hazardous reactions: Will not occur.
- 10.4 Conditions to avoid: None
- 10.5 Incompatible materials: None

10.6 Hazardous decomposition products: Welding fumes and gases cannot be classified simply. The composition and quantity of both are dependent upon the metal being welded, the process, procedure and welding consumables used. Other conditions which also influence the composition and quantity of the fumes and gases to which workers may be exposed include: coating on the metal being welded (i.e. paint, painting, galvanizing), the number of welders, the volume of the work area, the quality and the amount of ventilation, the position of the welders head with respect to the fume plume, as well as the presence of contaminants in the atmosphere (such as chlorinated hydrocarbon vapors from the cleaning and degreasing activities).

When an electrode is consumed, the fume and gas decomposition products generated are different in percent and form from the ingredients listed in Section 3. Fume and gas decomposition, and not the ingredients in the electrode, are important. The concentration of a given fume or gas component may decrease or increase by many times the original concentration. Also, new compounds not in the electrodes may form. Decomposition products of normal operation include those originating from the volatilization, reaction or oxidation of the materials shown in Section 3, plus those from the base metal coating, etc., as noted above. Reasonable expected fume constituents of this product would include: Complex oxides of iron, manganese, silicon, chromium, nickel, columbium, molybdenum, copper, carbon dioxide, carbon monoxide, ozone and nitrogen oxides. Some products will also contain antimony, barium, molybdenum, aluminum, columbium, magnesium, strontium, tungsten, and or zirconium. Fume limit for chromium, nickel and or manganese may be reached before limit of 5 mg/m3 of general welding fumes is reached.

Gaseous reaction products may include carbon monoxide and carbon dioxide. Ozone and nitrogen oxides may be formed by the radiation from the arc. Determine the composition and quantity of fumes and gases to which workers are exposed by taking an air sample from inside the welder's helmet if worn or in the worker's breathing zone. Improve ventilation if exposures are not below limits. See ANSI/AWES F1.1, F1.3 and F1.5, available from the American Welding Society, 550 N.W. Lejeune Road, Miami, FL 33126.

SECTION: 11 TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects:

Acute toxicity: Harmful if swallowed

Substance name	CAS number	LD50 oral rat (mg/kg)	ATE (oral) (mg/kg)	Comments
Iron	7439-89-6	984 mg/kg	984.000 mg/kg	
Nickel	7440-02-0	> 9000 mg/kg		
Silicon	7440-21-3		3160.000 mg/kg	
Manganese	7439-96-5		9000000.000 mg/kg	
Carbon	7440-44-0	> 10000 mg/kg		



SAFETY DATA SHEET 5 of 7

Skin corrosion/irritation:		Not classified			
Serious eye damage/irrita	tion:	Not classified	Not classified		
Respiratory or skin sensiti	zation:	May cause an allergic skin reaction.			
Germ cell mutagenicity:		Not classified			
Carcinogenicity:		May cause cancer.			
Substance name	CAS number				
Nickel	7440-02-0	I ARC Group	2B Possibly carcinogenic to humans		
		National Toxicology Program (NAP) Status	3- Reasonably anticapated to be Human Carcinogen		
Reproductive toxicity:		Not classified			
Specific target organ toxic	city (single exposure):	Not classified			
Specific target organ toxic	city (repeated exposur	e): Causes damage to organs thr	ough prolonged or repeated exposure.		
Aspiration hazard:		Not classified			
SECTION: 12	ECOLOGICAL INF	ORMATION			
12.1 Toxicity:					
-	general: Very toxic to	aquatic life.			
Nickel	(CAS No)	7440-02-0			
LC50 fishes 1		g/l (Exposure time: 96 h - Species: Brachydanio	rerio)		
EC50 Daphnia 1		g/I (Exposure time: 48 h - Species: Daphnia ma			
EC50 other aquatic organisms			osure time: 72 h - Species: Pseudokirchneriella subcapitata)		
LC50 fish 2			sure time: 96 h - Species: Cyprinus carpio [semi-static])		
EC50 Daphnia 2		Exposure time: 48 h - Species: Daphnia magna [
EC50 other aquatic organisms	9 .	0.311 mg/l (Exposure time: 96 h - Species: Pseu			
		- · ·			
Copper	(CAS No)	7440-50-8			
LC50 fishes 1		0.0156 mg/l (Exposure time: 96 h - Species: Pin			
EC50 Daphnia 1	-	(1 (Exposure time: 48 h - Species: Daphnia magr			
EC50 other aquatic organisms		0.0535 mg/l (Exposure time: 72 h - Species: Ps	·		
LC50 fish 2		g/l (Exposure time: 96 h - Species: Pimephales p			
EC50 other aquatic organisms	2 0.031 - 0	0.054 mg/l (Exposure time: 96 h - Species: Pseu	Idokirchneriella subcapitata [static])		
		additional information available.			
	-	itional information available.			
,	No additional inform				
12.5 Other adverse e	effects: No additiona	Il information available.			
SECTION: 13	DISPOSAL CONSI	DERATIONS			
13.1 Waste treatment methods: Dispose of in accordance with local and national regulations. Waste disposal recommendations: Dispose of contents/container in accordance with local/regional/national/international regulations.					
SECTION: 14	TRANSPORT INFO	DRMATION			
In accordance with DO)T / ADR / RID / AI	DNR / IMDG / ICAO / IATA			
14.1 UN Number: Not a dangerous good in sense of transport regulations					
14.2 UN proper shipping name: Not applicable					

SECTION: 15

REGULATORY INFORMATION

15.1 US Federal Regulations:

Iron	(CAS No)	7439-89-6
Listed on the United States TSC	A (Toxic Substances	Control Act) inventory
Nickel	(CAS No)	7440-02-0
Listed on the United States TSC Listed on SARA Section 313 (Sp	•	, ,
SARA Section 313 - Emission Reporting 0.1%		



SAFETY DATA SHEET 6 of 7

Silicon 7440-21-3 (CAS No) Listed on the United States TSCA (Toxic Substances Control Act) inventory Manganese (CAS No) 7439-96-5 Listed on the United States TSCA (Toxic Substances Control Act) inventory Listed on SARA Section 313 (Specific toxic chemical listings) SARA Section 313 - Emission Reporting 1.0% Carbon (CAS No) 7440-44-0 Listed on the United States TSCA (Toxic Substances Control Act) inventory (CAS No) Aluminum 7429-90-5 Listed on the United States TSCA (Toxic Substances Control Act) inventory Listed on SARA Section 313 (Specific toxic chemical listings) SARA Section 313 - Emission Reporting 1.0 % (dust or fume only) 7440-50-8 Copper (CAS No) Listed on the United States TSCA (Toxic Substances Control Act) inventory Listed on SARA Section 313 (Specific toxic chemical listings) SARA Section 313 - Emission Reporting 1.0%

15.2 US State Regulations:

Nickel	(CAS No) 7440-02	-0		
U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Reproductive Toxicity - Male	No significance risk level (NSRL)
Yes				
Nickel	(CAS No) 7440-02	-0		
U.S Massachusetts - Right To k U.S Minnesota - Hazardous Sut U.S New Jersey - Right to Knov U.S Pennsylvania - RTK (Right	bstance List w Hazardous Substance List			
Silicon	(CAS No) 7440-21	-3		
U.S Massachusetts - Right To k U.S Minnesota - Hazardous Suk U.S New Jersey - Right to Know U.S Pennsylvania - RTK (Right	ostance List w Hazardous Substance List			
Manganese	(CAS No) 7439-96	-5		
U.S Massachusetts - Right To k U.S Minnesota - Hazardous Suk U.S New Jersey - Right to Know U.S Pennsylvania - RTK (Right	bstance List w Hazardous Substance List			
Aluminum	(CAS No) 7429-90	-5		
U.S Massachusetts - Right To K U.S Minnesota - Hazardous Suk U.S New Jersey - Right to Know U.S Pennsylvania - RTK (Right	bstance List w Hazardous Substance List			
Copper	(CAS No) 7440-50	-8		
U.S Massachusetts - Right To k U.S Minnesota - Hazardous Sut U.S New Jersey - Right to Knov	bstance List			



SAFETY DATA SHEET 7 of 7

SECTION: 16

OTHER INFORMATION


Full text of H-phrases:

Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4	
Aquatic Acute 1	Hazardous to the aquatic environment — Acute Hazard, Category 1	
Aquatic Chronic 3	Hazardous to the aquatic environment — Chronic Hazard, Category 3	
Carc. 1B	Carcinogenicity, Category 1B	
Skin Sens. 1	Sensitisation — Skin, category 1	
STOT RE 1	Specific target organ toxicity — Repeated exposure, Category 1	
H302	Harmful if swallowed	
H317	May cause an allergic skin reaction	
H350	May cause cancer	
H372	Causes damage to organs through prolonged or repeated exposure	
H400	Very toxic to aquatic life	
H412	Harmful to aquatic life with long lasting effects.	

NFPA health hazard:

1 - Exposure could cause irritation but only minor residual injury even if no treatment is given.

- 0 Materials that will not burn.
- NFPA fire hazard: NFPA reactivity:
- 0 Normally stable, even under fire exposure conditions, and are not reactive with water.



HMIS III Rating

Health:	2 Moderate Hazard - Temporary or minor injury may occur
Flammability:	0 Minimal Hazard
Physical:	0 Minimal Hazard

We believe that the information contained herein is believed to be true and accurate as of the date of this SDS. All statements or suggestions are made without any warranty, expressed or implied, regarding the accuracy of the information, the hazard connected with the use of this material or the results to be obtained for use thereof. As the condition or methods of use are beyond our control, we do not assume any responsibility and expressly disclaim any liability for any use of this material. It is the user's obligation to determine the conditions of safe use of these products.

All chemical products can in fact present unknown risks to health, safety and / or the environment, even in relation to the different operating conditions, and they must therefore be used with care. For this reason we cannot guarantee that the risk described in this form are the only foreseeable risks. The user must therefore satisfy himself as to the particular conditions under which it is intended to be use in. Moreover, it must be noted that the user is obliged to comply with all the legislative, administrative and regulatory provisions regarding the product and its use in terms of occupational hygiene and safety, and environmental protection, apart from the information given in the form, given purely as guidance. **Technical Department**

1/6/2015